

OPERATION PERMIT

Hammond Department of Environmental Management
Air Pollution Control Division
5925 Calumet Avenue
Hammond, Indiana 46320-2598
(219) 853-6306

Permit #
03706

Linde Gas NA, LLC
3930 Michigan Street
Hammond, Indiana 46323

Stack ID

Spray Paint Booth

This unit is used to paint gas cylinders and welding machine parts. Particulate emissions from overspray of paint are controlled by polyester panel filters. Filters rated at 99.5% control efficiency.

The emissions shall be at a level acceptable to the regulations listed below for the following pollutants.

<u>POLLUTANT</u>	<u>EMISSION LIMIT</u>	<u>REGULATION</u>
PM	0.009 lbs/hr 0.039 TPY	Hammond Air Quality Control Ordinance No. 3522 (as amended)
PM10	0.009 lbs/hr 0.039 TPY	Hammond Air Quality Control Ordinance No. 3522 (as amended)
VOC	2.275 lbs/hr 9.965 TPY	Hammond Air Quality Control Ordinance No. 3522 (as amended)
		326 IAC 8-2-9

This permit, with the attached conditions, is issued under provisions of Hammond Ordinances No. 4621 and No. 7102 which incorporates by reference those standards found in 326 IAC and Hammond Ordinance No. 3522 (as amended).

Account No.: 2530

Date Issued: February 2, 2016

Expiration Date: December 31, 2016

Issued By:

Ronald L. Novak, Director

General Operation Conditions

1. That the data and information supplied in the application shall be considered part of this permit. Prior to any change in the operation, the change must be approved by the Hammond Department of Environmental Management (HDEM).
2. That the permittee shall comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder.
3. That the permittee shall comply with the provisions of the Hammond Environmental Management Ordinance No. 7102 which incorporates by reference those standards found in 326 Indiana Administrative Code (IAC).

Preventive Maintenance Plan

4. That pursuant to 326 IAC 1-6-3 (Preventive Maintenance Plans), the Company shall prepare and maintain a preventive maintenance plan, including the following information:
 - (a) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices.
 - (b) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions.
 - (c) Identification and quantification of the replacement parts which will be maintained in inventory for quick replacement.

The preventive maintenance plan shall be submitted to HDEM upon request and shall be subject to review and approval.

Malfunction

5. In the event that there should be a malfunction or breakdown of any of the following: fuel burning unit, combustion unit, incineration unit, process and/or other related process equipment and air pollution control equipment the Company shall notify the Department no later than four (4) business hours as specified in Article VI, Section 6.12 Hammond Air Quality Control Ordinance No. 3522 (as amended). Also, any emission of air contaminants or increase of emissions that may contribute to a violation of the Nuisance Abatement Regulation under the City of Hammond Air Quality Control Ordinance No. 3522 (as amended) Article VI, Section 6.11 shall also be reported within four (4) business hours.
6. That pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):
 - (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the HDEM or appointed representative upon request.
 - (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to HDEM. Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
 - (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
 - (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

Hammond Department of Environmental Management
- Air Pollution Control Division -

Opacity Limitation

7. That pursuant to 326 IAC 5-1-2 (Opacity Limitations) except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall not exceed an average of twenty percent (20%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-2.
8. The Company shall make available to HDEM all normal process operating records necessary to conduct the functions of the Department. Records of products produced, processed, material handled, and any other data related to the permitted source shall be kept for at least the past three (3) year period and shall be made available for inspection within five (5) business days after receipt of written notification of a request for inspection of said records.

Transfer of Permit

9. (a) In the event that ownership of this Company is changed, the source shall notify HDEM within thirty (30) days of the change. Notification shall include the date or proposed date of said change.
- (b) The written notification shall be sufficient to transfer the permit from the previous owner to the new owner.
- (c) The HDEM shall reserve the right to issue a new permit.

Permit Revocation

10. That pursuant to 326 IAC 2-1.1-9 (Revocation), this permit to construct or operate may be revoked for any of the following causes:
- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of HDEM the fact that continuance of this permit is not consistent with purposes of 326 IAC 2-1.1 (Permit Review Rules).

Inspection and Entry

11. Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow HDEM or an authorized representative to perform the following:
- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and

Hammond Department of Environmental Management
- Air Pollution Control Division -

- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

Availability of Permit

12. The Permittee shall maintain the applicable permit on the premises of this source and shall make this permit available for inspection by the HDEM or other public official having jurisdiction.

Special Operation Conditions

for

Linde Gas NA, LLC

Spray Paint Booth Operation

1. Linde Gas NA, LLC shall be required to record daily usage of (VOC) coatings applied in gallons for each day of operation. Linde Gas NA, LLC shall submit to the Hammond Department of Environmental Management - Air Pollution Control Division such records in a quarterly report, within fifteen (15) days after the end of each quarter. This data shall be submitted on the format attached.
2. Use of the spray paint booth for any other units, rates, or coatings other than those applied for and on record with this Department, must be approved by this Department.
3. Linde Gas NA, LLC shall only operate the spray paint booth with the polyester panel filters in place and in good working order.
4. Linde Gas NA, LLC shall not cause any emissions from the spray paint booth or the shotblast booth to create any nuisance or odors as specified in the City of Hammond Air Quality Control Ordinance #3522 (as amended), Article VI, Section 6.11 - Nuisance Abatement.

Volatile Organic Compound (VOC) Limitations

5. That pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coatings applied to metal gas cylinders shall be limited to 3.5 pounds VOC per gallon of coating less water.

Emission Minimization

6. That pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), solvent sprayed from the application equipment during clean up or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

Volatile Organic Compound

7. That pursuant to 326 IAC 2-1-3(i)(8), records of surface coating quantities and organic solvent contents shall be maintained for a minimum period of 36 months and made available upon request of the Hammond Department of Environmental Management (HDEM). Any change or modification, which may increase potential emissions from the source, shall submit an application for the modification before any changes are made.

Shotblast Cabinet Operation

8. That pursuant to 326 IAC 6-3 (Process Operations), the Dust Collector (DC-1) shall be in operation at all times when Shotblast Booth is in operation.
 - (a) An inspection shall be performed each calendar quarter of all the dust collector bags. Defective dust collector bags shall be replaced. A record shall be kept of the results of the inspection and the number of dust collector bags replaced.
 - (b) In the event that a dust collector's failure has been observed, the affected compartments will be shut down immediately until the failed units have been replaced.

**HAMMOND DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
AIR POLLUTION CONTROL DIVISION
DAILY (VOC) USAGE**

Paint - gallons/day

COMPANY NAME: Linde Gas NA, LLC
LOCATION: 3930 Michigan Street, Hammond

MONTH/YEAR: _____

DAY	GALLONS
1	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	

DAY	GALLONS
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	

Total usage per month _____ gallons.

I hereby certify that no other surface coating was applied as specified in our permit application on file.

Submitted by: _____

Date: _____