

SPONSOR: Mark Kalwinski
1st District Councilman

ORDINANCE NO. 9296

AN ORDINANCE TO ESTABLISH RULES AND REGULATIONS FOR THE DISCHARGE OF WASTEWATER INTO THE WASTEWATER TREATMENT SYSTEMS OF THE SANITARY DISTRICT OF HAMMOND

WHEREAS, The Hammond Sanitary District, on March 10, 2015 did pass and approve Resolution 13-2015, which established rules and regulations for the discharge of wastewater in the treatment systems of the District (Exhibit 1); and

WHEREAS, it is required that the City of Hammond and the Town of Munster pass Pre Treatment Ordinances, and attached to and made a part of this Ordinance is a Pre-Treatment Ordinance approved by the Hammond Sanitary District (Exhibit 2); and

WHEREAS, the United States Environmental Protection Agency (USEPA) has approved the attached Pre-Treatment Ordinance, which is required by State and Federal environmental regulations; and

WHEREAS, The Hammond Common Council now desires that the attached Pre-Treatment Ordinance be approved and such Ordinance as written, repeal and replace any pre-existing Ordinances in the City of Hammond as to the discharge of wastewater into the Hammond Sanitary District's treatment system; and

THEREFORE BE IT ORDAINED by the Common Council of the City of Hammond that the rules and regulations for the discharge of wastewater into the Hammond Sanitary District's treatment, as contained in the attached Pre-Treatment Ordinance, be adopted and approved for the users of the Sanitary District.

FURTHER BE IT ORDAINED by the Common Council of the City of Hammond that this Ordinance shall become effective upon its passage by the Hammond Common Council,

**AN ORDINANCE TO ESTABLISH RULES AND REGULATIONS FOR THE
DISCHARGE OF WASTEWATER INTO THE WASTEWATER TREATMENT
SYSTEMS OF THE SANITARY DISTRICT OF HAMMOND**

signing by its President, and approval of the Mayor.

Michael Opinker, President /s/
Hammond Common Council

ATTEST:

Robert J. Golec, City Clerk /s/

PRESENTED BY ME, the undersigned City Clerk of the City of Hammond to the Mayor of said City for his approval on the 26th day of May, 2015.

Robert J. Golec, City Clerk /s/


The foregoing Ordinance No. 9296 consisting of two (2) typewritten pages, including this page was approved by the Mayor on the 26th day of May, 2015.

Thomas M. McDermott, Jr. Mayor /s/
City of Hammond, Indiana

PASSED BY THE Common Council on the 26th day of May, 2015 and approved by the Mayor on the 26th day of May, 2015.

Robert J. Golec, City Clerk /s/

SANITARY DISTRICT of HAMMOND



PRETREATMENT ORDINANCE

TABLE OF CONTENTS

	Page
SECTION 1—GENERAL PROVISIONS	1
1.1 Purpose and Policy	1
1.2 Administration	2
1.3 Abbreviations	2
1.4 Definitions	2
SECTION 2—GENERAL SEWER USE REQUIREMENTS	9
2.1 Prohibited Discharge Standards	9
2.2 National Categorical Pretreatment Standards	11
2.3 State Pretreatment Standards	14
2.4 Local Limits	14
2.5 HSD’s Right of Revision	15
2.6 Dilution	15
SECTION 3—PRETREATMENT OF WASTEWATER	15
3.1 Pretreatment Facilities	15
3.2 Additional Pretreatment Measures	16
3.3 Accidental Discharge/Slug Discharge Control Plans	16
3.4 Hauled Wastewater	17
SECTION 4—INDIVIDUAL WASTEWATER DISCHARGE PERMITS and GENERAL PERMITS	17
4.1 Wastewater Analysis	17
4.2 Individual Wastewater Discharge Permit and General Permit Requirement	18
4.3 Individual Wastewater Discharge and General Permitting: Existing Connections	18
4.4 Individual Wastewater Discharge and General Permitting: New Connections	18
4.5 Individual Wastewater Discharge and General Permit Application Contents	19
4.6 Wastewater Discharge Permitting: General Permits	20
4.7 Wastewater Discharge Permitting: Temporary Permits	21
4.8 Application Signatories and Certifications	22
4.9 Individual Wastewater Discharge and General Permit Decisions	22
SECTION 5—INDIVIDUAL WASTEWATER DISCHARGE AND GENERAL PERMIT ISSUANCE	22
5.1 Individual Wastewater Discharge and General Permit Duration	22
5.2 Individual Wastewater Discharge Permit and General Permit Contents	22
5.3 Permit Modification	24
5.4 Individual Wastewater Discharge Permit and General Permit Transfer	25
5.5 Individual Wastewater Discharge Permit and General Permit Revocation	25
5.6 Individual Wastewater Discharge Permit and General Permit Reissuance	26
5.7 Regulation of Waste Received from Other Jurisdictions	27

SECTION 6—REPORTING REQUIREMENTS	28
6.1 Baseline Monitoring Reports	28
6.2 Compliance Schedule Progress Reports	29
6.3 Reports on Compliance with Categorical Pretreatment Standard Deadline	30
6.4 Periodic Compliance Reports	30
6.5 Reports of Changed Conditions	32
6.6 Reports of Potential Problems	32
6.7 Reports from Unpermitted Users	33
6.8 Notice of Violation/Repeat Sampling and Reporting	33
6.9 Notification of the Discharge of Hazardous Waste	34
6.10 Analytical Requirements	35
6.11 Sample Collection	35
6.12 Date of Receipt of Reports	36
6.13 Recordkeeping	36
6.14 Certification Statements	36
SECTION 7—COMPLIANCE MONITORING	37
7.1 Right of Entry: Inspection and Sampling	37
SECTION 8—CONFIDENTIAL INFORMATION	38
SECTION 9—PUBLICATION OF USERS IN SIGNIFICANT NONCOMPLIANCE	39
SECTION 10—ADMINISTRATIVE ENFORCEMENT REMEDIES	40
10.1 Notification of Violation	40
10.2 Consent Orders	40
10.3 Show Cause Hearing	41
10.4 Compliance Orders	41
10.5 Cease and Desist Orders	41
10.6 Administrative Fines	42
10.7 Emergency Suspensions	42
10.8 Termination of Discharge	43
10.9 Falsifying of Information/ Tampering	43
SECTION 11—JUDICIAL ENFORCEMENT REMEDIES	44
11.1 Injunctive Relief	44
11.2 Civil Penalties	44
11.3 Criminal Prosecution	44
11.4 Remedies Nonexclusive	45
SECTION 12—AFFIRMATIVE DEFENSES TO DISCHARGE VIOLATIONS	45
12.1 Upset	45
12.2 Prohibited Discharge Standards	46
12.3 Bypass	46

SECTION 13—WASTEWATER TREATMENT RATES - [RESERVED]	48
SECTION 14—MISCELLANEOUS PROVISIONS	48
14.1 Pretreatment Charges and Fees	48
14.2 Administrative Appeal	49
14.3 Severability	49
14.4 Recovery of Costs Incurred by the District and/or City	49
SECTION 15—EFFECTIVE DATE	50

SANITARY DISTRICT OF HAMMOND PRETREATMENT ORDINANCE

ORDINANCE NO. []

SECTION 1—GENERAL PROVISIONS

1.1 Purpose and Policy

This ordinance sets forth uniform requirements for Users of the Publicly Owned Treatment Works for the Sanitary District of Hammond and enables the Sanitary District of Hammond to comply with all applicable State and Federal laws, including the Clean Water Act (33 United States Code [U.S.C.] section 1251 et seq.) and the General Pretreatment Regulations (Title 40 of the *Code of Federal Regulations* [CFR] Part 403). The objectives of this ordinance are:

- A. To prevent the introduction of pollutants into the Publicly Owned Treatment Works that will interfere with its operation;
- B. To prevent the introduction of pollutants into the Publicly Owned Treatment Works that will pass through the Publicly Owned Treatment Works, inadequately treated, into receiving waters, or otherwise be incompatible with the Publicly Owned Treatment Works;
- C. To protect both Publicly Owned Treatment Works personnel who may be affected by wastewater and sludge in the course of their employment and the general public;
- D. To promote reuse and recycling of industrial wastewater and sludge from the Publicly Owned Treatment Works; and
- E. To enable Sanitary District of Hammond to comply with its National Pollutant Discharge Elimination System permit conditions, sludge use and disposal requirements, and any other Federal or State laws to which the Publicly Owned Treatment Works is subject.

This Ordinance shall apply to the Sanitary District of Hammond and to communities outside the District who are, by contract or agreement with the District, Users of the District's Publicly Owned Treatment Works. The ordinance authorizes the issuance of individual wastewater discharge permits or general permits; provides for monitoring, compliance, and enforcement activities; establishes administrative review procedures; requires User reporting; and provides for the setting of fees for the equitable distribution of costs resulting from the program established herein.

1.2 Administration

Except as otherwise provided herein, the Pretreatment Coordinator of the Sanitary District of Hammond shall administer, implement, and enforce the provisions of this ordinance. Any powers granted to or duties imposed upon the Pretreatment Coordinator may be assumed by the District Manager of the Sanitary District of Hammond.

1.3 Abbreviations

The following abbreviations, when used in this ordinance, shall have the designated meanings:

BMP – Best Management Practice
BMR – Baseline Monitoring Report
CBOD – Carbonaceous Biochemical Oxygen Demand
CFR – *Code of Federal Regulations*
CIU – Categorical Industrial User
COD – Chemical Oxygen Demand
EPA – U.S. Environmental Protection Agency
GPD – Gallons per Day
HSD – Sanitary District of Hammond (Hammond Sanitary District)
IDEM – Indiana Department of Environmental Management
IU – Industrial User
MG/L – Milligrams
per Liter
NPDES – National Pollutant Discharge Elimination System
POTW – Publicly Owned Treatment Works
RCRA – Resource Conservation and Recovery Act
SIU – Significant Industrial User
SNC – Significant Noncompliance
TKN – Total Kjeldahl Nitrogen
TSS – Total Suspended Solids
U.S.C. – United States Code

1.4 Definitions

Unless a provision explicitly states otherwise, the following terms and phrases, as used in this ordinance, shall have the meanings hereinafter designated.

- A. Act or “the Act.” The Federal Water Pollution Control Act, also known as the Clean Water Act, as amended, 33 U.S.C. section 1251 et seq.
- B. Approval Authority. The Administrator of Region V of the EPA.

C. Authorized or Duly Authorized Representative of the User.

(1) If the User is a corporation:

(a) The president, secretary, treasurer, or a vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation; or

(b) The manager of one or more manufacturing, production, or operating facilities, provided the manager is authorized to make management decisions that govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiate and direct other comprehensive measures to assure long-term environmental compliance with environmental laws and regulations; can ensure that the necessary systems are established or actions taken to gather complete and accurate information for individual wastewater discharge permit or general permit requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

(2) If the User is a partnership or sole proprietorship: a general partner or proprietor, respectively.

(3) If the User is a Federal, State, or local governmental facility: a director or highest official appointed or designated to oversee the operation and performance of the activities of the government facility, or their designee.

(4) The individuals described in paragraphs 1 through 3, above, may designate a Duly Authorized Representative if the authorization is in writing, the authorization specifies the individual or position responsible for the overall operation of the facility from which the discharge originates or having overall responsibility for environmental matters for the company, and the written authorization is submitted to the Sanitary District of Hammond.

D. Best Management Practices or BMPs. Schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to implement the prohibitions listed in Section 2.1 A and B [40 CFR 403.5(a)(1) and (b)]. BMPs include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw materials storage.

E. Carbonaceous Biochemical Oxygen Demand. The quantity of dissolved oxygen in milligrams per liter (mg/l) required during microbiological stabilization of the decomposable carbonaceous organic matter by aerobic biochemical action through the addition of a nitrification inhibitor and incubation under standard laboratory procedures for five (5) days at 20 degrees Celsius.

F. Categorical Pretreatment Standard or Categorical Standard. Any regulation containing pollutant discharge limits promulgated by EPA in accordance with sections 307(b) and (c) of the Act (33 U.S.C. section 1317) that apply to a specific category of Users and that appear in 40 CFR Chapter I, Subchapter N, Parts 405-471.

G. Categorical Industrial User. An Industrial User subject to a categorical Pretreatment Standard or categorical Standard.

H. Chemical Oxygen Demand or COD. The quantity of oxygen, expressed in milligrams per liter (mg/l), required to oxidize the organic and oxidizable inorganic substances in a waste sample under specific conditions of oxidizing agent, temperature, and time.

I. Control Authority. The Sanitary District of Hammond Indiana.

J. Daily Maximum. The arithmetic average of all effluent samples for a pollutant collected during a calendar day.

K. Daily Maximum Limit. The maximum allowable discharge limit of a pollutant during a calendar day. Where Daily Maximum Limits are expressed in units of mass, the daily discharge is the total mass discharged over the course of the day. Where Daily Maximum Limits are expressed in terms of a concentration, the daily discharge is the arithmetic average measurement of the pollutant concentration derived from all measurements taken that day.

L. District Manager. The person designated by Sanitary District of Hammond to supervise the operation of the POTW, and who is charged with certain duties and responsibilities by this ordinance.

M. Environmental Protection Agency or EPA. The U.S. Environmental Protection Agency or, where appropriate, the Regional Water Management Division Director, the Regional Administrator, or other duly authorized official of said agency.

N. Existing Source. Any source of discharge that is not a "New Source."

O. Grab Sample. A sample that is taken from a wastestream without regard to the flow in the wastestream and over a period of time not to exceed fifteen (15) minutes.

P. Indiana Department of Environmental Management or IDEM. The Indiana Department of Environmental Management or, where appropriate, the Commissioner, or other duly authorized official of said agency.

Q. Indirect Discharge or Discharge. The introduction of pollutants into the POTW from any nondomestic source.

R. Instantaneous Limit. The maximum concentration of a pollutant allowed to be discharged at any time, determined from the analysis of any discrete or composited sample collected, independent of the industrial flow rate and the duration of the sampling event

S. Interference. A discharge that, alone or in conjunction with a discharge or discharges from other sources, inhibits or disrupts the POTW, its treatment processes or operations or its sludge processes, use or disposal; and therefore, is a cause of a violation of HSD's NPDES permit or of the prevention of sewage sludge use or disposal in compliance with any of the following statutory/regulatory provisions or permits issued thereunder, or any more stringent State or local regulations: section 405 of the Act; the Solid Waste Disposal Act, including Title II commonly referred to as the Resource Conservation and Recovery Act (RCRA); any State regulations contained in any State sludge management plan prepared pursuant to Subtitle D of the Solid Waste Disposal Act; the Clean Air Act; the Toxic Substances Control Act; and the Marine Protection, Research, and Sanctuaries Act.

T. Local Limit. Specific discharge limits developed and enforced by the Sanitary District of Hammond upon industrial or commercial facilities to implement the general and specific discharge prohibitions listed in 40 CFR 403.5(a)(1) and (b).

U. Medical Waste. Isolation wastes, infectious agents, human blood and blood products, pathological wastes, sharps, body parts, contaminated bedding, surgical wastes, potentially contaminated laboratory wastes, and dialysis wastes.

V. Monthly Average. The sum of all "daily discharges" measured during a calendar month divided by the number of "daily discharges" measured during that month.

W. Monthly Average Limit. The highest allowable average of "daily discharges" over a calendar month, calculated as the sum of all "daily discharges" measured during a calendar month divided by the number of "daily discharges" measured during that month.

X. New Source. (1) Any building, structure, facility, or installation from which there is (or may be) a discharge of pollutants, the construction of which commenced after the publication of proposed Pretreatment Standards under section 307(c) of the Act that will be applicable to such source if such Standards are thereafter promulgated in accordance with that section, provided that:

- (a) The building, structure, facility, or installation is constructed at a site at which no other source is located; or
- (b) The building, structure, facility, or installation totally replaces the process or production equipment that causes the discharge of pollutants at an Existing Source; or
- (c) The production or wastewater generating processes of the building, structure, facility, or installation are substantially independent of an Existing Source at the same site. In determining whether these are substantially independent, factors such as the extent to which the new facility is integrated with the existing plant, and the extent to which the new facility is engaged in the same general type of activity as the Existing Source, should be considered.

(2) Construction on a site at which an Existing Source is located results in a modification rather than a New Source if the construction does not create a new building, structure, facility, or installation meeting the criteria of Section (1)(b) or (c) above but otherwise alters, replaces, or adds to existing process or production equipment.

(3) Construction of a New Source as defined under this paragraph has commenced if the owner or operator has:

(a) Begun, or caused to begin, as part of a continuous onsite construction program

- (i) any placement, assembly, or installation of facilities or equipment; or
- (ii) significant site preparation work including clearing, excavation, or removal of existing buildings, structures, or facilities which is necessary for the placement, assembly, or installation of new source facilities or equipment; or

(b) Entered into a binding contractual obligation for the purchase of facilities or equipment which are intended to be used in its operation within a reasonable time. Options to purchase or contracts which can be terminated or modified without substantial loss, and contracts for feasibility, engineering, and design studies do not constitute a contractual obligation under this paragraph.

Y. Noncontact Cooling Water. Water used for cooling that does not come into direct contact with any raw material, intermediate product, waste product, or finished product.

Z. Pass Through. A discharge which exits the POTW into waters of the United States in quantities or concentrations which, alone or in conjunction with a discharge or discharges from other sources, is a cause of a violation of any requirement of HSD's NPDES permit, including an increase in the magnitude or duration of a violation.

AA. Person. Any individual, partnership, copartnership, firm, company, corporation, association, joint stock company, trust, estate, governmental entity, or any other legal entity; or their legal representatives, agents, or assigns. This definition includes all Federal, State, and local governmental entities.

BB. pH. A measure of the acidity or alkalinity of a solution, expressed in standard units.

CC. Pollutant. Dredged spoil, solid waste, incinerator residue, filter backwash, sewage, garbage, sewage sludge, munitions, Medical Wastes, chemical wastes, biological materials, radioactive materials, heat, wrecked or discarded equipment, rock, sand, cellar dirt, municipal, agricultural and industrial wastes, and certain characteristics of wastewater (e.g., pH, temperature, TSS, turbidity, color, BOD, COD, toxicity, or odor).

DD. Pretreatment. The reduction of the amount of pollutants, the elimination of pollutants, or the alteration of the nature of pollutant properties in wastewater prior to, or in lieu of, introducing such pollutants into the POTW. This reduction or alteration can be obtained by physical, chemical, or biological processes; by process changes; or by other means, except by diluting the concentration of the pollutants unless allowed by an applicable Pretreatment Standard.

EE. Pretreatment Coordinator. The person designated by Sanitary District of Hammond to supervise the Pretreatment Department of the POTW, and who is charged with certain duties and responsibilities by this ordinance.

FF. Pretreatment Requirements. Any substantive or procedural requirement related to pretreatment imposed on a User, other than a Pretreatment Standard.

GG. Pretreatment Standards or Standards. Pretreatment Standards shall mean prohibited discharge standards, categorical Pretreatment Standards, and Local Limits.

HH. Prohibited Discharge Standards or Prohibited Discharges. Absolute prohibitions against the discharge of certain substances; these prohibitions appear in Section 2.1 of this ordinance.

II. Publicly Owned Treatment Works or POTW. A treatment works, as defined by section 212 of the Act (33 U.S.C. section 1292), which is owned by the Sanitary District of Hammond. This definition includes any devices or systems used in the collection, storage, treatment, recycling, and reclamation of sewage or industrial wastes of a liquid nature and any conveyances, which convey wastewater to a treatment plant.

JJ. Septic Tank Waste. Any sewage from holding tanks such as vessels, chemical toilets, campers, trailers, and septic tanks.

KK. Sewage. Human excrement and gray water (household showers, dishwashing operations, etc.).

LL. Significant Industrial User (SIU).

Except as provided in paragraphs (3) and (4) of this Section, a Significant Industrial User is:

(1) An Industrial User subject to categorical Pretreatment Standards; or

(2) An Industrial User that:

(a) Discharges an average of twenty-five thousand (25,000) gpd or more of process wastewater to the POTW (excluding sanitary, noncontact cooling and boiler blowdown wastewater);

(b) Contributes a process wastestream which makes up five (5) percent or more of the average dry weather hydraulic or organic capacity of the POTW treatment plant; or

(c) Is designated as such by HSD on the basis that it has a reasonable potential for adversely affecting the POTW's operation or for violating any Pretreatment Standard or Requirement.

MM. Significant Noncompliance (SNC). A violation which:

(a) Occurs in 66% or more of the samples taken over a six (6) month period (any magnitude);

(b) Exceeds the Technical Review Criteria (TRC) for the same discharge limit for 33% or more of the samples taken over a six (6) month period [TRC =1.4 (40% exceedance) for CBOD, TSS, Fats, Oils and Grease; TRC =1.2 (20% exceedance) for all other pollutants except pH];

(c) Causes, alone or in combination with other discharges, interference or pass through, including endangering POTW personnel or public;

(d) Endangers human health or the environment, or results in the POTW's exercise of its emergency powers;

- (e) A delay in meeting a Compliance Schedule Milestone (failure to begin or complete construction or attain final compliance) by 90 days or more;
- (f) Failure to report noncompliance;
- (g) Any other significant violation(s); or
- (h) Failure to submit any required report within 30 days of the due date.

NN. Significant Violation. A violation which:

- (a) Is continuous or frequent;
- (b) Results in known environmental or District POTW damage;
- (c) Was considered “nonsignificant” and has remained uncorrected for 30 days or more;
- (d) Will result in other violations;
- (e) Has no good or valid cause; or
- (f) Has evidence of negligence or intent.

OO. Slug Load or Slug Discharge. Any discharge at a flow rate or concentration, which could cause a violation of the prohibited discharge standards in Section 2.1 of this ordinance. A Slug Discharge is any Discharge of a non-routine, episodic nature, including but not limited to an accidental spill or a non-customary batch Discharge, which has a reasonable potential to cause Interference or Pass Through, or in any other way violate the POTW’s regulations, Local Limits or Permit conditions.

PP. Storm Water. Any flow occurring during or following any form of natural precipitation, and resulting from such precipitation, including snowmelt.

QQ. Total Suspended Solids or Suspended Solids. The total suspended matter that floats on the surface of, or is suspended in, water, wastewater, or other liquid, and that is removable by laboratory filtering.

RR. User or Industrial User. A source of indirect discharge.

SS. Wastewater. Liquid and water-carried industrial wastes and sewage from residential dwellings, commercial buildings, industrial and manufacturing facilities, and institutions, whether treated or untreated, which are contributed to the POTW.

TT. Wastewater Treatment Plant or Treatment Plant. That portion of the POTW which is designed to provide treatment of municipal sewage and industrial waste.

SECTION 2—GENERAL SEWER USE REQUIREMENTS

2.1 Prohibited Discharge Standards

A. General Prohibitions. No User shall introduce or cause to be introduced into the POTW any pollutant or wastewater which causes Pass Through or Interference. These general prohibitions apply to all Users of the POTW whether or not they are subject to categorical Pretreatment Standards or any other National, State, or local Pretreatment Standards or Requirements.

B. Specific Prohibitions. No User shall introduce or cause to be introduced into the POTW the following pollutants, substances, or wastewater:

(1) Pollutants which create a fire or explosive hazard in the POTW, including, but not limited to, wastestreams with a closed-cup flashpoint of less than 140 degrees F (60 degrees C) using the test methods specified in 40 CFR 261.21;

(2) Wastewater having a pH less than 5.0 or more than 11.5, or otherwise causing corrosive structural damage to the POTW or equipment;

(3) Solid or viscous substances in amounts which will cause obstruction of the flow in the POTW resulting in Interference [but in no case solids greater than one half inch (1/2") in any dimension];

(4) Pollutants, including oxygen-demanding pollutants (COD, etc.), released in a discharge at a flow rate and/or pollutant concentration which, either singly or by interaction with other pollutants, will cause Interference with the POTW;

(5) Wastewater having a temperature greater than 150 degrees F (65 degrees C)], or which will inhibit biological activity in the treatment plant resulting in Interference, but in no case wastewater which causes the temperature at the introduction into the treatment plant to exceed 104 degrees F (40 degrees C);

(6) Petroleum oil, nonbiodegradable cutting oil, or products of mineral oil origin, in amounts that will cause Interference or Pass Through;

(7) Pollutants which result in the presence of toxic gases, vapors, or fumes within the POTW in a quantity that may cause acute worker health and safety problems;

(8) Trucked or hauled pollutants, except at discharge points designated by the District Manager in accordance with Section 3.4 of this ordinance;

(9) Noxious or malodorous liquids, gases, solids, or other wastewater which, either singly or by interaction with other wastes, are sufficient to create a public nuisance or a hazard to life, or to prevent entry into the sewers for maintenance or repair;

- (10) Wastewater which imparts color which cannot be removed by the treatment process, such as, but not limited to, dye wastes and vegetable tanning solutions, which consequently imparts color to the treatment plant's effluent, thereby violating HSD's NPDES permit;
- (11) Wastewater containing any radioactive wastes or isotopes except in compliance with applicable State or Federal regulations;
- (12) Storm Water, surface water, ground water, artesian well water, roof runoff, subsurface drainage, swimming pool drainage, condensate, deionized water, Noncontact Cooling Water, and unpolluted wastewater, unless specifically authorized by Pretreatment Coordinator or District Manager;
- (13) Sludges, screenings, or other residues from the pretreatment of industrial wastes unless specifically authorized by the Pretreatment Coordinator or District Manager;
- (14) Medical Wastes, except as specifically authorized by Pretreatment Coordinator or District Manager in an individual wastewater discharge permit or a general permit;
- (15) Wastewater causing, alone or in conjunction with other sources, the treatment plant's effluent to fail toxicity test;
- (16) Detergents, surface-active agents, or other substances which that might cause excessive foaming in the POTW;
- (17) Fats, oils, or greases of animal or vegetable origin or petroleum oil, non-biodegradable cutting oil or products of mineral in quantities to produce a visible free floating or separate layer or in such quantities as to interfere with the normal operation of the POTW, require special treatment or leave deposits on pipe walls, tanks, etc.
- (18) Wastewater causing any readings on an explosion hazard meter at the point of discharge into the POTW, or at any point in the POTW, of more than ten percent (10%) of the Lower Explosive Limit of the meter.

Pollutants, substances, or wastewater prohibited by this Section shall not be processed or stored in such a manner that they could be discharged to the POTW.

2.2 National Categorical Pretreatment Standards

Users must comply with the categorical Pretreatment Standards found at 40 CFR Chapter I, Subchapter N, Parts 405–471.

A. Where a categorical Pretreatment Standard is expressed only in terms of either the mass or the concentration of a pollutant in wastewater, the Pretreatment Coordinator may impose equivalent concentration or mass limits in accordance with Section 2.2D and 2.2E.

B. When the limits in a categorical Pretreatment Standard are expressed only in terms of mass of pollutant per unit of production, the Pretreatment Coordinator may convert the limits to equivalent limitations expressed either as mass of pollutant discharged per day or effluent concentration for purposes of calculating effluent limitations applicable to individual Industrial Users.

C. When wastewater subject to a categorical Pretreatment Standard is mixed with wastewater not regulated by the same Standard, the Pretreatment Coordinator shall impose an alternate limit in accordance with 40 CFR 403.6(e).

D. When a categorical Pretreatment Standard is expressed only in terms of pollutant concentrations, an Industrial User may request that the Sanitary District of Hammond convert the limits to equivalent mass limits. The determination to convert concentration limits to mass limits is within the discretion of the Pretreatment Coordinator. The Sanitary District of Hammond may establish equivalent mass limits only if the Industrial User meets all the conditions set forth in Sections 2.2D(1)(a) through 2.2D(1)(e) below.

- (1) To be eligible for equivalent mass limits, the Industrial User must:
 - a. Employ, or demonstrate that it will employ, water conservation methods and technologies that substantially reduce water use during the term of its individual wastewater discharge permit;
 - b. Currently use control and treatment technologies adequate to achieve compliance with the applicable categorical Pretreatment Standard, and not have used dilution as a substitute for treatment;
 - c. Provide sufficient information to establish the facility's actual average daily flow rate for all wastestreams, based on data from a continuous effluent flow monitoring device, as well as the facility's long-term average production rate. Both the actual average daily flow rate and the long-term average production rate must be representative of current operating conditions;
 - d. Not have daily flow rates, production levels, or pollutant levels that vary so significantly that equivalent mass limits are not appropriate to control the Discharge; and
 - e. Have consistently complied with all applicable categorical Pretreatment Standards during the period prior to the Industrial User's request for equivalent mass limits.
- (2) An Industrial User subject to equivalent mass limits must:
 - a. Maintain and effectively operate control and treatment technologies adequate to achieve compliance with the equivalent mass limits;

- b. Continue to record the facility's flow rates through the use of a continuous effluent flow monitoring device;
- c. Continue to record the facility's production rates and notify the Pretreatment Coordinator whenever production rates are expected to vary by more than 20 percent from its baseline production rates determined in paragraph 2.2F(1)(c) of this Section. Upon notification of a revised production rate, the Pretreatment Coordinator will reassess the equivalent mass limit and revise the limit as necessary to reflect changed conditions at the facility; and
- d. Continue to employ the same or comparable water conservation methods and technologies as those implemented pursuant to paragraphs 2.2E(1)(a) of this Section so long as it discharges under an equivalent mass limit.

- (3) When developing equivalent mass limits, the Pretreatment Coordinator:
 - a. Will calculate the equivalent mass limit by multiplying the actual average daily flow rate of the regulated process(es) of the Industrial User by the concentration-based Daily Maximum and Monthly Average Standard for the applicable categorical Pretreatment Standard and the appropriate unit conversion factor;
 - b. Upon notification of a revised production rate, will reassess the equivalent mass limit and recalculate the limit as necessary to reflect changed conditions at the facility; and
 - c. May retain the same equivalent mass limit in subsequent individual wastewater discharger permit terms if the Industrial User's actual average daily flow rate was reduced solely as a result of the implementation of water conservation methods and technologies, and the actual average daily flow rates used in the original calculation of the equivalent mass limit were not based on the use of dilution as a substitute for treatment pursuant to Section 2.6. The Industrial User must also be in compliance with Section 12.3 regarding the prohibition of bypass.

E. The Pretreatment Coordinator may convert the mass limits of the categorical Pretreatment Standards of 40 CFR Parts 414, 419, and 455 to concentration limits for purposes of calculating limitations applicable to individual Industrial Users. The conversion is at the discretion of the Pretreatment Coordinator.

F. Once included in its permit, the Industrial User must comply with the equivalent limitations developed in this Section (2.2) in lieu of the promulgated categorical Standards from which the equivalent limitations were derived.

G. Many categorical Pretreatment Standards specify one limit for calculating maximum daily discharge limitations and a second limit for calculating maximum Monthly Average, or 4-day average, limitations. Where such Standards are being applied, the same production or flow figure shall be used in calculating both the average and the maximum equivalent limitation.

I. Any Industrial User operating under a permit incorporating equivalent mass or concentration limits calculated from a production-based Standard shall notify the Pretreatment Coordinator within two (2) business days after the User has a reasonable basis to know that the production level will significantly change within the next calendar month. Any User not notifying the Pretreatment Coordinator of such anticipated change will be required to meet the mass or concentration limits in its permit that were based on the original estimate of the long term average production rate.

2.3 State Pretreatment Standards

Users must comply with State of Indiana Pretreatment Standards codified at 327 IAC 5-18-8, 327 IAC 5-18-9 and 327 IAC 5-18-10.

2.4 Local Limits

A. The Pretreatment Coordinator or District Manager is authorized to establish Local Limits pursuant to 40 CFR 403.5(c).

B. The following pollutant limits are established to protect against Pass Through and Interference. No person shall discharge wastewater containing in excess of the following Daily Maximum Limits:

<u>Parameter</u>	<u>Limit (mg/l)</u>
1,1,1-Trichloroethane	1.6
1, 2 Dichlorethane	1.1
Benzene	0.13
Cadmium	0.33
Chloride	2,800.0
Chromium	7.0
Copper	5.0
Cyanide, Total	9.0
Ethyl Benzene	1.6
Iron, Dissolved	3.9
Lead	1.6
Mercury	0.033
Methylene Chloride	4.2
Nickel, Total	9.3
Oil and/or grease, Total	600.0
PCB's	Less than the method detection limit for approved test procedures listed in the most current 40 CFR Part 136, Appendix A
Phenols, Total	1.3
Surfactants [MBAS]	680.0
Toluene	1.4
Xylenes, Total	2.0
Zinc	5.0

The above limits apply at the point where the wastewater is discharged to the POTW. All concentrations for metallic substances are for total metal unless indicated otherwise. The Pretreatment Coordinator or District Manger may impose mass limitations in addition to the concentration-based limitations above.

C. The Pretreatment Coordinator may develop Best Management Practices (BMPs), by ordinance or in individual wastewater discharge permits or general permits, to implement Local Limits and the requirements of Section 2.1.

D. The Pretreatment Coordinator may develop site specific limitations in individual wastewater discharge permits or general permits to prevent overloading of the POTW.

2.5 The Sanitary District of Hammond's Right of Revision

The Sanitary District of Hammond reserves the right to establish, by ordinance or in individual wastewater discharge permits or in general permits, more stringent Standards or Requirements on discharges to the POTW consistent with the purpose of this ordinance.

2.6 Dilution

No User shall ever increase the use of process water, or in any way attempt to dilute a discharge, as a partial or complete substitute for adequate treatment to achieve compliance with a discharge limitation unless expressly authorized by an applicable Pretreatment Standard or Requirement. The Pretreatment Coordinator may impose mass limitations on Users who are using dilution to meet applicable Pretreatment Standards or Requirements, or in other cases when the imposition of mass limitations is appropriate.

SECTION 3—PRETREATMENT OF WASTEWATER

3.1 Pretreatment Facilities

Users shall provide wastewater treatment as necessary to comply with this ordinance and shall achieve compliance with all categorical Pretreatment Standards, Local Limits, and the prohibitions set out in Section 2.1 of this ordinance within the time limitations specified by EPA, the State, or the Pretreatment Coordinator, whichever is more stringent. Any facilities necessary for compliance shall be provided, operated, and maintained at the User's expense. Detailed plans describing such facilities and operating procedures shall be submitted to Pretreatment Coordinator for review, and shall be acceptable to Pretreatment Coordinator before such facilities are constructed. The review of such plans and operating procedures shall in no way relieve the User

from the responsibility of modifying such facilities as necessary to produce a discharge acceptable to the HSD under the provisions of this ordinance.

3.2 Additional Pretreatment Measures

A. Whenever deemed necessary, the Pretreatment Coordinator may require Users to restrict their discharge during peak flow periods, designate that certain wastewater be discharged only into specific sewers, relocate and/or consolidate points of discharge, separate sewage wastestreams from industrial wastestreams, and such other conditions as may be necessary to protect the POTW and determine the User's compliance with the requirements of this ordinance.

B. The Pretreatment Coordinator may require any person discharging into the POTW to install and maintain, on their property and at their expense, a suitable storage and flow-control facility to ensure equalization of flow. An individual wastewater discharge permit or a general permit may be issued solely for flow equalization.

C. Grease, oil, and sand interceptors shall be provided when, in the opinion of the Pretreatment Coordinator, they are necessary for the proper handling of wastewater containing excessive amounts of grease and oil, or sand; except that such interceptors shall not be required for residential users. All interception units shall be of a type and capacity approved the Pretreatment Coordinator shall be so located to be easily accessible for cleaning and inspection. Such interceptors shall be inspected, cleaned, and repaired by the User at their expense.

D. Users with the potential to discharge flammable substances may be required to install and maintain an approved combustible gas detection meter.

3.3 Accidental Discharge/Slug Discharge Control Plans

The Pretreatment Coordinator shall evaluate whether each SIU needs an accidental discharge/slug discharge control plan or other action to control Slug Discharges. The Pretreatment Coordinator may require any User to develop, submit for approval, and implement such a plan or take such other action that may be necessary to control Slug Discharges. An accidental discharge/slug discharge control plan shall address, at a minimum, the following:

A. Description of discharge practices, including non-routine batch discharges;

B. Description of stored chemicals;

C. Procedures for immediately notifying the Pretreatment Coordinator of any accidental or Slug Discharge, as required by Section 6.6 of this ordinance; and

D. Procedures to prevent adverse impact from any accidental or Slug Discharge. Such procedures include, but are not limited to, inspection and maintenance of storage areas, handling and transfer of materials, loading and unloading operations, control of plant site runoff, worker training, building of containment structures or equipment, measures for containing toxic organic pollutants, including solvents, and/or measures and equipment for emergency response.

3.4 Hauled Wastewater

A. Septic tank waste may be introduced into the POTW only at locations designated by the District Manager, and at such times as are established by the District Manager. Such waste shall not violate Section 2 of this ordinance or any other requirements established by the HSD. The District Manager may require haulers of septic waste to obtain individual wastewater discharge permits or general permits.

B. The District Manager may require haulers of industrial waste to obtain individual wastewater discharge permits or general permits. The District Manager may require generators of hauled industrial waste to obtain individual wastewater discharge permits or general permits. The District Manager also may prohibit the disposal of hauled industrial waste. The discharge of hauled industrial waste is subject to all other requirements of this ordinance.

C. Industrial waste haulers may discharge loads only at locations designated by the District Manager. No load may be discharged without prior consent of the District Manager. The District Manager may collect samples of each hauled load to ensure compliance with applicable Standards. The District Manager may require the industrial waste hauler to provide a waste analysis of any load prior to discharge.

D. Industrial waste haulers must provide a waste-tracking form for every load. This form shall include, at a minimum, the name and address of the industrial waste hauler, permit number, truck identification, names and addresses of sources of waste, and volume and characteristics of waste. The form shall identify the type of industry, known or suspected waste constituents, and whether any wastes are RCRA hazardous wastes.

SECTION 4—INDIVIDUAL WASTEWATER DISCHARGE PERMITS and GENERAL PERMITS

4.1 Wastewater Analysis

When requested by the Pretreatment Coordinator, a User must submit information on the nature and characteristics of its wastewater within thirty (30) days of the request. The Pretreatment Coordinator is authorized to prepare a form for this purpose and may periodically require Users to update this information.

4.2 Individual Wastewater Discharge Permit and General Permit Requirement

A. No Significant Industrial User shall discharge wastewater into the POTW without first obtaining an individual wastewater discharge permit or a general permit from the Pretreatment Coordinator, except that a Significant Industrial User that has filed a timely application pursuant to Section 4.3 of this ordinance may continue to discharge for the time period specified therein.

B. The Pretreatment Coordinator may require other Users to obtain individual wastewater discharge permits or general permits as necessary to carry out the purposes of this ordinance.

C. Any violation of the terms and conditions of an individual wastewater discharge permit or a general permit shall be deemed a violation of this ordinance and subjects the wastewater discharge permittee to the sanctions set out in Sections 10 through 12 of this ordinance. Obtaining an individual wastewater discharge permit or a general permit does not relieve a permittee of its obligation to comply with all Federal and State Pretreatment Standards or Requirements or with any other requirements of Federal, State, and local law.

4.3 Individual Wastewater Discharge and General Permitting: Existing Connections

Any User required to obtain an individual wastewater discharge permit or a general permit who was discharging wastewater into the POTW prior to the effective date of this ordinance and who wishes to continue such discharges in the future, shall, within forty-five (45) days after said date, apply to the Pretreatment Coordinator for an individual wastewater discharge permit or a general permit in accordance with Section 4.5 of this ordinance, and shall not cause or allow discharges to the POTW to continue after one hundred eighty (180) days of the effective date of this ordinance except in accordance with an individual wastewater discharge permit or a general permit issued by the Pretreatment Coordinator.

4.4 Individual Wastewater Discharge and General Permitting: New Connections

Any User required to obtain an individual wastewater discharge permit or a general permit who proposes to begin or recommence discharging into the POTW must obtain such permit prior to the beginning or recommencing of such discharge. An application for this individual wastewater discharge permit or general permit in accordance with Section 4.5 of this ordinance, one hundred eighty (180) days prior to the date upon which any discharge will begin or recommence.

4.5 Individual Wastewater Discharge and General Permit Application Contents

A. All Users required to obtain an individual wastewater discharge permit or a general permit must submit a permit application. Users that are eligible may request a general permit under Section 4.6. The Pretreatment Coordinator may require Users to submit all or some of the following information as part of a permit application:

- (1) Identifying Information.
 - a. The name and address of the facility, including the name of the operator and owner.
 - b. Contact information, description of activities, facilities, and plant production processes on the premises;
- (2) Environmental Permits. A list of any environmental control permits held by or for the facility.
- (3) Description of Operations.
 - a. A brief description of the nature, average rate of production (including each product produced by type, amount, processes, and rate of production), and standard industrial classifications of the operation(s) carried out by such User. This description should include a schematic process diagram, which indicates points of discharge to the POTW from the regulated processes.
 - b. Types of wastes generated, and a list of all raw materials and chemicals used or stored at the facility which are, or could accidentally or intentionally be, discharged to the POTW;
 - c. Number and type of employees, hours of operation, and proposed or actual hours of operation;
 - d. Type and amount of raw materials processed (average and maximum per day);
 - e. Site plans, floor plans, mechanical and plumbing plans, and details to show all sewers, floor drains, and appurtenances by size, location, and elevation, and all points of discharge;
- (4) Time and duration of discharges;
- (5) The location for monitoring all wastes covered by the permit;
- (6) Flow Measurement. Information showing the measured average daily and maximum daily flow, in gallons per day, to the POTW from regulated process streams and other streams, as necessary, to allow use of the combined wastestream formula set out in Section 2.2C (40 CFR 403.6(e)).

(7) Measurement of Pollutants.

- a. The categorical Pretreatment Standards applicable to each regulated process and any new categorically regulated processes for Existing Sources.
- b. The results of sampling and analysis identifying the nature and concentration, and/or mass, where required by the Standard or by the Pretreatment Coordinator, of regulated pollutants in the discharge from each regulated process.
- c. Instantaneous, Daily Maximum, and long-term average concentrations, or mass, where required, shall be reported.
- d. The sample shall be representative of daily operations and shall be analyzed in accordance with procedures set out in Section 6.10 of this ordinance. Where the Standard requires compliance with a BMP or pollution prevention alternative, the User shall submit documentation as required by the Pretreatment Coordinator or the applicable Standards to determine compliance with the Standard.
- e. Sampling must be performed in accordance with procedures set out in Section 6.11 of this ordinance.

(8) Any request to be covered by a general permit based on Section 4.6.

(9) Any other information as may be deemed necessary by the Pretreatment Coordinator to evaluate the permit application.

B. Incomplete or inaccurate applications will not be processed and will be returned to the User for revision.

4.6 Wastewater Discharge Permitting: General Permits

A. At the discretion of the Pretreatment Coordinator, the Pretreatment Coordinator may use general permits to control SIU discharges to the POTW if the following conditions are met. All facilities to be covered by a general permit must:

- (1) Involve the same or substantially similar types of operations;
- (2) Discharge the same types of wastes;
- (3) Require the same effluent limitations;
- (4) Require the same or similar monitoring; and
- (5) In the opinion of the Pretreatment Coordinator, are more appropriately controlled under a general permit than under individual wastewater discharge permits.

B. To be covered by the general permit, the SIU must file a written request for coverage that identifies its contact information, production processes, the types of wastes generated, the location for monitoring all wastes covered by the general permit, any requests in accordance with Section 6.4B for a monitoring

waiver for a pollutant neither present nor expected to be present in the Discharge, and any other information the POTW deems appropriate. A monitoring waiver for a pollutant neither present nor expected to be present in the discharge is not effective in the general permit until after the Pretreatment Coordinator has provided written notice to the SIU that such a waiver request has been granted in accordance with Section 6.4B.

C. The Pretreatment Coordinator will retain a copy of the general permit, documentation to support the POTW's determination that a specific SIU meets the criteria in Section 4.6A(1) to (5) and applicable State regulations, and a copy of the User's written request for coverage for three (3) years after the expiration of the general permit.

D. The Pretreatment Coordinator may not control an SIU through a general permit where the facility is subject to production-based categorical Pretreatment Standards or categorical Pretreatment Standards expressed as mass of pollutant discharged per day or for IUs whose limits are based on the Combined Wastestream Formula (Section 2.2C).

4.7 Wastewater Discharge Permitting: Temporary Permits

Any temporary user, prior to proceeding with a dewatering project shall request, in written form, permission to discharge to the Sanitary District of Hammond sewer system. Written requests should be submitted to the Pretreatment Coordinator Thirty (30) days prior to the project start date.

The following information is to be included in said request:

- A. Name, address of applicant and location of dewatering site;
- B. Wastewater constituents and characteristics mentioned in Sections 2.1 and 2.3; and Section 2.4 of this Ordinance as determined by an accredited analytical laboratory in accordance with Section 6.10 of this Ordinance;
- C. Time, duration and approximate volume of the discharge.

If all criteria is acceptable to the Pretreatment Coordinator, a temporary permit may be issued. A temporary permit shall expire Thirty (30) days after date of issuance. The permit is subject to all rules and regulations of this Ordinance. If a permitted project continues past the expiration date of the temporary permit, the permit may, if deemed acceptable by the District, be renewed for another Thirty (30) days. The renewed permit may be subject to additional permit fees.

Temporary Permit Fee: \$100.00

Temporary Permit Flow Charge: Commercial Rate

Significant Industrial Users (SIU's) are not eligible for temporary permits.

4.8 Application Signatories and Certifications

A. All wastewater discharge permit applications, User reports and certification statements must be signed by an Authorized Representative of the User and contain the certification statement in Section 6.14A.

B. If the designation of an Authorized Representative is no longer accurate because a different individual or position has responsibility for the overall operation of the facility or overall responsibility for environmental matters for the company, a new written authorization satisfying the requirements of this Section must be submitted to the Pretreatment Coordinator prior to or together with any reports to be signed by an Authorized Representative.

4.9 Individual Wastewater Discharge and General Permit Decisions

The Pretreatment Coordinator will evaluate the data furnished by the User and may require additional information. Within ninety (90) days of receipt of a complete permit application, the Pretreatment Coordinator will determine whether to issue an individual wastewater discharge permit or a general permit. The Pretreatment Coordinator may deny any application for an individual wastewater discharge permit or a general permit.

SECTION 5—INDIVIDUAL WASTEWATER DISCHARGE AND GENERAL PERMIT ISSUANCE

5.1 Individual Wastewater Discharge and General Permit Duration

An individual wastewater discharge permit or a general permit shall be issued for a specified time period, not to exceed five (5) years from the effective date of the permit. An individual wastewater discharge permit or a general permit may be issued for a period less than five (5) years, at the discretion of the Pretreatment Coordinator. Each individual wastewater discharge permit or a general permit will indicate a specific date upon which it will expire.

5.2 Individual Wastewater Discharge Permit and General Permit Contents

An individual wastewater discharge permit or a general permit shall include such conditions as are deemed reasonably necessary by the Pretreatment Coordinator to prevent Pass Through or Interference, protect the quality of the water body receiving the treatment plant's effluent, protect worker health and safety, facilitate sludge management and disposal, and protect against damage to the POTW.

A. Individual wastewater discharge permits and general permits must contain:

- (1) A statement that indicates the wastewater discharge permit issuance date, expiration date and effective date;

- (2) A statement that the wastewater discharge permit is nontransferable without prior notification to the Sanitary District of Hammond in accordance with Section 5.4 of this ordinance, and provisions for furnishing the new owner or operator with a copy of the existing wastewater discharge permit;
- (3) Effluent limits, including Best Management Practices, based on applicable Pretreatment Standards;
- (4) Self monitoring, sampling, reporting, notification, and record-keeping requirements. These requirements shall include an identification of pollutants (or best management practice) to be monitored, sampling location, sampling frequency, and sample type based on Federal, State, and local law.
- (5) A statement of applicable civil and criminal penalties for violation of Pretreatment Standards and Requirements, and any applicable compliance schedule. Such schedule may not extend the time for compliance beyond that required by applicable Federal, State, or local law.
- (6) Requirements to control Slug Discharge, if determined by the Pretreatment Coordinator to be necessary.

B. Individual wastewater discharge permits or general permits may contain, but need not be limited to, the following conditions:

- (1) Limits on the average and/or maximum rate of discharge, time of discharge, and/or requirements for flow regulation and equalization;
- (2) Requirements for the installation of pretreatment technology, pollution control, or construction of appropriate containment devices, designed to reduce, eliminate, or prevent the introduction of pollutants into the treatment works;
- (3) Requirements for the development and implementation of spill control plans or other special conditions including management practices necessary to adequately prevent accidental, unanticipated, or nonroutine discharges;
- (4) Development and implementation of waste minimization plans to reduce the amount of pollutants discharged to the POTW;
- (5) The unit charge or schedule of User charges and fees for the management of the wastewater discharged to the POTW;

- (6) Requirements for installation and maintenance of inspection and sampling facilities and equipment, including flow measurement devices;
- (7) A statement that compliance with the individual wastewater discharge permit or the general permit does not relieve the permittee of responsibility for compliance with all applicable Federal and State Pretreatment Standards, including those which become effective during the term of the individual wastewater discharge permit or the general permit; and
- (8) Other conditions as deemed appropriate by the Pretreatment Coordinator to ensure compliance with this ordinance, and State and Federal laws, rules, and regulations.

5.3 Permit Modification

A. The Pretreatment Coordinator may modify an individual wastewater discharge permit for good cause, including, but not limited to, the following reasons:

- (1) To incorporate any new or revised Federal, State, or local Pretreatment Standards or Requirements;
- (2) To address significant alterations or additions to the User's operation, processes, or wastewater volume or character since the time of the individual wastewater discharge permit issuance;
- (3) A change in the POTW that requires either a temporary or permanent reduction or elimination of the authorized discharge;
- (4) Information indicating that the permitted discharge poses a threat to the Sanitary District of Hammond's POTW, HSD personnel, beneficial sludge use or the receiving waters;
- (5) Violation of any terms or conditions of the individual wastewater discharge permit;
- (6) Misrepresentations or failure to fully disclose all relevant facts in the wastewater discharge permit application or in any required reporting;
- (7) Revision of or a grant of variance from categorical Pretreatment Standards pursuant to 40 CFR 403.13;
- (8) To correct typographical or other errors in the individual wastewater discharge permit; or

- (9) To reflect a transfer of the facility ownership or operation to a new owner or operator where requested in accordance with Section 5.4.

B. The Pretreatment Coordinator may modify a general permit for good cause, including, but not limited to, the following reasons:

- (1) To incorporate any new or revised Federal, State, or local Pretreatment Standards or Requirements;
- (2) A change in the POTW that requires either a temporary or permanent reduction or elimination of the authorized discharge;
- (3) To correct typographical or other errors in the individual wastewater discharge permit; or
- (4) To reflect a transfer of the facility ownership or operation to a new owner or operator where requested in accordance with Section 5.4.

5.4 Individual Wastewater Discharge Permit and General Permit Transfer

Individual wastewater discharge permits or coverage under general permits may be transferred to a new owner or operator only if the permittee gives at least ninety (90) days advance notice to the Pretreatment Coordinator and the Pretreatment Coordinator approves the individual wastewater discharge permit or the general permit coverage transfer. The notice to the Pretreatment Coordinator must include a written certification by the new owner or operator which:

- A. States that the new owner and/or operator has no immediate intent to change the facility's operations and processes;
- B. Identifies the specific date on which the transfer is to occur; and
- C. Acknowledges full responsibility for complying with the existing individual wastewater discharge permit or general permit.

Failure to provide advance notice of a transfer renders the individual wastewater discharge permit or coverage under the general permit void as of the date of facility transfer.

5.5 Individual Wastewater Discharge Permit and General Permit Revocation

The Pretreatment Coordinator may revoke an individual wastewater discharge permit or coverage under a general permit for good cause, including, but not limited to, the following reasons:

- A. Failure to notify Pretreatment Coordinator of significant changes to the wastewater prior to the changed discharge;
- B. Failure to provide prior notification to Pretreatment Coordinator of changed conditions pursuant to Section 6.5 of this ordinance;
- C. Misrepresentation or failure to fully disclose all relevant facts in the wastewater discharge permit application;
- D. Falsifying self-monitoring reports and certification statements;
- E. Tampering with monitoring equipment;
- F. Refusing to allow the Pretreatment Coordinator, or designee, timely access to the facility premises and records;
- G. Failure to meet effluent limitations;
- H. Failure to pay fines;
- I. Failure to pay sewer charges;
- J. Failure to meet compliance schedules;
- K. Failure to complete a wastewater survey or the wastewater discharge permit application;
- L. Failure to provide advance notice of the transfer of business ownership of a permitted facility; or
- M. Violation of any Pretreatment Standard or Requirement, or any terms of the wastewater discharge permit or the general permit or this ordinance.

Individual wastewater discharge permits or coverage under general permits shall be voidable upon cessation of operations or transfer of business ownership. All individual wastewater discharge permits issued to a User are void upon the issuance of a new individual wastewater discharge permit or a general permit to that User.

5.6 Individual Wastewater Discharge Permit and General Permit Reissuance

A User with an expiring individual wastewater discharge permit or general permit shall apply for individual wastewater discharge permit or general permit reissuance by submitting a complete permit application, in accordance with Section 4.5 of this ordinance, a minimum of one hundred eighty(180) days prior to the expiration of the User's existing individual wastewater discharge permit or general permit.

5.7 Regulation of Waste Received from Other Jurisdictions

A. If another municipality, or User located within another municipality, contributes wastewater to the POTW, the District Manager (upon direction of the Board of Sanitary Commissioners) shall enter into an intermunicipal agreement with the contributing municipality.

B. Prior to entering into an agreement required by paragraph A, above, the District Manager shall request the following information from the contributing municipality:

- (1) A description of the quality and volume of wastewater discharged to the POTW by the contributing municipality;
- (2) An inventory of all Users located within the contributing municipality that are discharging to the POTW; and
- (3) Such other information as the District Manager may deem necessary.

C. An intermunicipal agreement, as required by paragraph A, above, shall contain the following conditions:

- (1) A requirement for the contributing municipality to adopt a sewer use ordinance which is at least as stringent as this ordinance and Local Limits, including required Baseline Monitoring Reports (BMRs) which are at least as stringent as those set out in Section 2.4 of this ordinance. The requirement shall specify that such ordinance and limits must be revised as necessary to reflect changes made to the Sanitary District of Hammond ordinance or Local Limits;
- (2) A requirement for the contributing municipality to submit a revised User inventory on at least an annual basis;
- (3) A provision specifying which pretreatment implementation activities, including individual wastewater discharge permit or general permit issuance, inspection and sampling, and enforcement, will be conducted by the contributing municipality; which of these activities will be conducted by the Pretreatment Coordinator; and which of these activities will be conducted jointly by the contributing municipality and the Pretreatment Coordinator;
- (4) A requirement for the contributing municipality to provide the Pretreatment Coordinator with access to all information that the contributing municipality obtains as part of its pretreatment activities;

- (5) Limits on the nature, quality, and volume of the contributing municipality's wastewater at the point where it discharges to the POTW;
- (6) Requirements for monitoring the contributing municipality's discharge;
- (7) A provision ensuring the Pretreatment Coordinator, or designee, access to the facilities of Users located within the contributing municipality's jurisdictional boundaries for the purpose of inspection, sampling, and any other duties deemed necessary by the Pretreatment Coordinator, or designee; and
- (8) A provision specifying remedies available for breach of the terms of the intermunicipal agreement.

SECTION 6—REPORTING REQUIREMENTS

6.1 Baseline Monitoring Reports

A. Within either one hundred eighty (180) days after the effective date of a categorical Pretreatment Standard, or the final administrative decision on a category determination under 40 CFR 403.6(a)(4), whichever is later, existing Categorical Industrial Users currently discharging to or scheduled to discharge to the POTW shall submit to the Pretreatment Coordinator a report which contains the information listed in paragraph B, below. At least ninety (90) days prior to commencement of their discharge, New Sources, and sources that become Categorical Industrial Users subsequent to the promulgation of an applicable categorical Standard, shall submit to the Pretreatment Coordinator a report which contains the information listed in paragraph B, below. A New Source shall report the method of pretreatment it intends to use to meet applicable categorical Standards. A New Source also shall give estimates of its anticipated flow and quantity of pollutants to be discharged.

B. Users described above shall submit the information set forth below.

- (1) All information required in Section 4.5A(1)(a), Section 4.5A(2), Section 4.5A(3)(a), and Section 4.5A(6).
- (2) Measurement of pollutants.
 - a. The User shall provide the information required in Section 4.5A(7)(a) through (d).
 - b. The User shall take a minimum of one representative sample to compile that data necessary to comply with the requirements of this paragraph unless additional samples are required under Section 6.11.
 - c. Samples should be taken immediately downstream from pretreatment facilities if such exist or immediately downstream from the regulated

process if no pretreatment exists. If other wastewaters are mixed with the regulated wastewater prior to pretreatment the User should measure the flows and concentrations necessary to allow use of the combined wastestream formula in 40 CFR 403.6(e) to evaluate compliance with the Pretreatment Standards. Where an alternate concentration or mass limit has been calculated in accordance with 40 CFR 403.6(e) this adjusted limit along with supporting data shall be submitted to the Control Authority;

- d. Sampling and analysis shall be performed in accordance with Sections 6.10 and 6.11;
- e. The Pretreatment Coordinator may allow the submission of a baseline report which utilizes only historical data so long as the data provides information sufficient to determine the need for industrial pretreatment measures;
- f. The baseline report shall indicate the time, date and place of sampling and methods of analysis, and shall certify that such sampling and analysis is representative of normal work cycles and expected pollutant Discharges to the POTW.

(3) Compliance Certification. A statement, reviewed by the User's Authorized Representative as defined in Section 1.4C and certified by a qualified professional, indicating whether Pretreatment Standards are being met on a consistent basis, and, if not, whether additional operation and maintenance (O&M) and/or additional pretreatment is required to meet the Pretreatment Standards and Requirements.

(4) Compliance Schedule. If additional pretreatment and/or O&M will be required to meet the Pretreatment Standards, the shortest schedule by which the User will provide such additional pretreatment and/or O&M must be provided. The completion date in this schedule shall not be later than the compliance date established for the applicable Pretreatment Standard. A compliance schedule pursuant to this Section must meet the requirements set out in Section 6.2 of this ordinance.

(5) Signature and Report Certification. All baseline monitoring reports must be certified in accordance with Section 6.14A of this ordinance and signed by an Authorized Representative as defined in Section 1.4C.

6.2 Compliance Schedule Progress Reports

The following conditions shall apply to the compliance schedule required by Section 6.1(B)(4) of this ordinance:

- A. The schedule shall contain progress increments in the form of dates for the commencement and completion of major events leading to the construction and operation of additional pretreatment required for the User to meet the applicable

Pretreatment Standards (such events include, but are not limited to, hiring an engineer, completing preliminary and final plans, executing contracts for major components, commencing and completing construction, and beginning and conducting routine operation);

B. No increment referred to above shall exceed nine (9) months;

C. The User shall submit a progress report to the Pretreatment Coordinator no later than fourteen (14) days following each date in the schedule and the final date of compliance including, as a minimum, whether or not it complied with the increment of progress, the reason for any delay, and, if appropriate, the steps being taken by the User to return to the established schedule; and

D. In no event shall more than nine (9) months elapse between such progress reports to the Pretreatment Coordinator.

6.3 Reports on Compliance with Categorical Pretreatment Standard Deadline

Within ninety (90) days following the date for final compliance with applicable categorical Pretreatment Standards, or in the case of a New Source following commencement of the introduction of wastewater into the POTW, any User subject to such Pretreatment Standards and Requirements shall submit to the Pretreatment Coordinator a report containing the information described in Section 4.5A(6) and (7) and 6.1(B)(2) of this ordinance. For Users subject to equivalent mass or concentration limits established in accordance with the procedures in Section 2.2, this report shall contain a reasonable measure of the User's long-term production rate. For all other Users subject to categorical Pretreatment Standards expressed in terms of allowable pollutant discharge per unit of production (or other measure of operation), this report shall include the User's actual production during the appropriate sampling period. All compliance reports must be signed and certified in accordance with Section 6.14A of this ordinance. All sampling will be done in conformance with Section 6.11.

6.4 Periodic Compliance Reports

A. All Users must, at a frequency determined by the Pretreatment Coordinator submit no less than twice per year (June and December) reports indicating the nature, concentration of pollutants in the discharge which are limited by Pretreatment Standards and the measured or estimated average and maximum daily flows for the reporting period. In cases where the Pretreatment Standard requires compliance with a Best Management Practice (BMP) or pollution prevention alternative, the User must submit documentation required by the Pretreatment Coordinator or the Pretreatment Standard necessary to determine the compliance status of the User. All submittals shall include chain-of-custody forms.

B. The Sanitary District of Hammond may authorize an Industrial User subject to a categorical Pretreatment Standard to forego sampling of a pollutant regulated

by a categorical Pretreatment Standard if the Industrial User has demonstrated through sampling and other technical factors that the pollutant is neither present nor expected to be present in the Discharge, or is present only at background levels from intake water and without any increase in the pollutant due to activities of the Industrial User. [see 40 CFR 403.12(e)(2)] This authorization is subject to the following conditions:

- (1) The waiver may be authorized where a pollutant is determined to be present solely due to sanitary wastewater discharged from the facility provided that the sanitary wastewater is not regulated by an applicable categorical Standard and otherwise includes no process wastewater.
- (2) The monitoring waiver is valid only for the duration of the effective period of the individual wastewater discharge permit, but in no case longer than 5 years. The User must submit a new request for the waiver before the waiver can be granted for each subsequent individual wastewater discharge permit. See Section 4.5A.
- (3) In making a demonstration that a pollutant is not present, the Industrial User must provide data from at least one sampling of the facility's process wastewater prior to any treatment present at the facility that is representative of all wastewater from all processes.
- (4) The request for a monitoring waiver must be signed in accordance with Section 1.4C, and include the certification statement in 6.14 A (40 CFR 403.6(a)(2)(ii)).
- (5) Non-detectable sample results may be used only as a demonstration that a pollutant is not present if the EPA approved method from 40 CFR Part 136 with the lowest minimum detection level for that pollutant was used in the analysis.
- (6) Any grant of the monitoring waiver by the Pretreatment Coordinator must be included as a condition in the User's permit. The reasons supporting the waiver and any information submitted by the User in its request for the waiver must be maintained by the Pretreatment Coordinator for 3 years after expiration of the waiver.
- (7) Upon approval of the monitoring waiver and revision of the User's permit by the Pretreatment Coordinator, the Industrial User must certify on each report with the statement in Section 6.14 B below, that there has been no increase in the pollutant in its wastestream due to activities of the Industrial User.
- (8) In the event that a waived pollutant is found to be present or is expected to be present because of changes that occur in the User's operations, the

User must immediately: Comply with the monitoring requirements of Section 6.4A, or other more frequent monitoring requirements imposed by the Pretreatment Coordinator, and notify the Pretreatment Coordinator.

(9) This provision does not supersede certification processes and requirements established in categorical Pretreatment Standards, except as otherwise specified in the categorical Pretreatment Standard.

C. All periodic compliance reports must be signed and certified in accordance with Section 6.14A of this ordinance.

D. All wastewater samples must be representative of the User's discharge. Wastewater monitoring and flow measurement facilities shall be properly operated, kept clean, and maintained in good working order at all times. The failure of a User to keep its monitoring facility in good working order shall not be grounds for the User to claim that sample results are unrepresentative of its discharge.

E. If a User subject to the reporting requirement in this section monitors any regulated pollutant at the appropriate sampling location more frequently than required by the Pretreatment Coordinator, using the procedures prescribed in Section 6.11 of this ordinance, the results of this monitoring shall be included in the report.

6.5 Reports of Changed Conditions

Each User must notify the Pretreatment Coordinator of any significant changes to the User's operations or system which might alter the nature, quality, or volume of its wastewater at least Thirty (30) days before the change.

- A. The Pretreatment Coordinator may require the User to submit such information as may be deemed necessary to evaluate the changed condition, including the submission of a wastewater discharge permit application under Section 4.5 of this ordinance.
- B. The Pretreatment Coordinator may issue an individual wastewater discharge permit or a general permit under Section 5.7 of this ordinance or modify an existing wastewater discharge permit or a general permit under Section 5.4 of this ordinance in response to changed conditions or anticipated changed conditions.

6.6 Reports of Potential Problems

- A. In the case of any discharge, including, but not limited to, accidental discharges, discharges of a nonroutine, episodic nature, a noncustomary batch

discharge, a Slug Discharge or Slug Load, that might cause potential problems for the POTW, the User shall immediately telephone and notify the Pretreatment Coordinator of the incident. This notification shall include the location of the discharge, type of waste, concentration and volume, if known, and corrective actions taken by the User.

B. Within five (5) days following such discharge, the User shall, unless waived by the Pretreatment Coordinator, submit a detailed written report describing the cause(s) of the discharge and the measures to be taken by the User to prevent similar future occurrences. Such notification shall not relieve the User of any expense, loss, damage, or other liability which might be incurred as a result of damage to the POTW, natural resources, or any other damage to person or property; nor shall such notification relieve the User of any fines, penalties, or other liability which may be imposed pursuant to this ordinance.

C. A notice shall be permanently posted on the User's bulletin board or other prominent place advising employees who to call in the event of a discharge described in paragraph A, above. Employers shall ensure that all employees, who could cause such a discharge to occur, are advised of the emergency notification procedure.

D. Significant Industrial Users are required to notify the Pretreatment Coordinator immediately of any changes at its facility affecting the potential for a Slug Discharge.

6.7 Reports from Unpermitted Users

All Users not required to obtain an individual wastewater discharge permit or general permit shall provide appropriate reports to the Pretreatment Coordinator as the Pretreatment Coordinator may require.

6.8 Notice of Violation/Repeat Sampling and Reporting

If sampling performed by a User indicates a violation, the User must notify the Pretreatment Coordinator within twenty-four (24) hours of becoming aware of the violation. The User shall also repeat the sampling and analysis and submit the results of the repeat analysis to the Pretreatment Coordinator within thirty (30) days after becoming aware of the violation. Resampling by the Industrial User is not required if the HSD performs sampling at the User's facility at least once a month, or if the HSD performs sampling at the User between the time when the initial sampling was conducted and the time when the User or the HSD receives the results of this sampling, or if the HSD has performed the sampling and analysis in lieu of the Industrial User. If the HSD performed the sampling and analysis in lieu of the Industrial User, the HSD will perform the repeat sampling and analysis unless it notifies the User of the violation and requires the User to perform the repeat sampling and analysis.

6.9 Notification of the Discharge of Hazardous Waste

A. Any User who commences the discharge of hazardous waste shall notify the POTW, the EPA Regional Waste Management Division Director, and State hazardous waste authorities, in writing, of any discharge into the POTW of a substance which, if otherwise disposed of, would be a hazardous waste under 40 CFR Part 261. Such notification must include the name of the hazardous waste as set forth in 40 CFR Part 261, the EPA hazardous waste number, and the type of discharge (continuous, batch, or other). If the User discharges more than one hundred (100) kilograms of such waste per calendar month to the POTW, the notification also shall contain the following information to the extent such information is known and readily available to the User: an identification of the hazardous constituents contained in the wastes, an estimation of the mass and concentration of such constituents in the wastestream discharged during that calendar month, and an estimation of the mass of constituents in the wastestream expected to be discharged during the following twelve (12) months. All notifications must take place no later than one hundred and eighty (180) days after the discharge commences. Any notification under this paragraph need be submitted only once for each hazardous waste discharged. However, notifications of changed conditions must be submitted under Section 6.5 of this ordinance. The notification requirement in this Section does not apply to pollutants already reported by Users subject to categorical Pretreatment Standards under the self-monitoring requirements of Sections 6.1, 6.3, and 6.4 of this ordinance.

B. Dischargers are exempt from the requirements of paragraph A, above, during a calendar month in which they discharge no more than fifteen (15) kilograms of hazardous wastes, unless the wastes are acute hazardous wastes as specified in 40 CFR 261.30(d) and 261.33(e). Discharge of more than fifteen (15) kilograms of nonacute hazardous wastes in a calendar month, or of any quantity of acute hazardous wastes as specified in 40 CFR 261.30(d) and 261.33(e), requires a one-time notification. Subsequent months during which the User discharges more than such quantities of any hazardous waste do not require additional notification.

C. In the case of any new regulations under section 3001 of RCRA identifying additional characteristics of hazardous waste or listing any additional substance as a hazardous waste, the User must notify the District Manager, the EPA Regional Waste Management Waste Division Director, and State hazardous waste authorities of the discharge of such substance within ninety (90) days of the effective date of such regulations.

D. In the case of any notification made under this Section, the User shall certify that it has a program in place to reduce the volume and toxicity of hazardous wastes generated to the degree it has determined to be economically practical.

E. This provision does not create a right to discharge any substance not otherwise permitted to be discharged by this ordinance, a permit issued thereunder, or any applicable Federal or State law.

6.10 Analytical Requirements

All pollutant analyses, including sampling techniques, to be submitted as part of a wastewater discharge permit application or report shall be performed in accordance with the techniques prescribed in 40 CFR Part 136 and amendments thereto, unless otherwise specified in an applicable categorical Pretreatment Standard. If 40 CFR Part 136 does not contain sampling or analytical techniques for the pollutant in question, or where the EPA determines that the Part 136 sampling and analytical techniques are inappropriate for the pollutant in question, sampling and analyses shall be performed by using validated analytical methods or any other applicable sampling and analytical procedures, including procedures suggested by the Pretreatment Coordinator or other parties approved by EPA.

6.11 Sample Collection

Samples collected to satisfy reporting requirements must be based on data obtained through appropriate sampling and analysis performed during the period covered by the report, based on data that is representative of conditions occurring during the reporting period

A. Except as indicated in Section B and C below, the User must collect wastewater samples using 24-hour flow-proportional composite sampling techniques, unless time-proportional composite sampling or grab sampling is authorized by the Pretreatment Coordinator. Where time-proportional composite sampling or grab sampling is authorized by the HSD, the samples must be representative of the discharge. Using protocols (including appropriate preservation) specified in 40 CFR Part 136 and appropriate EPA guidance, multiple grab samples collected during a 24-hour period may be composited prior to the analysis as follows: for cyanide, total phenols, and sulfides the samples may be composited in the laboratory or in the field; for volatile organics and oil and grease, the samples may be composited in the laboratory. Composite samples for other parameters unaffected by the compositing procedures as documented in approved EPA methodologies may be authorized by the HSD, as appropriate. In addition, grab samples may be required to show compliance with Instantaneous Limits.

B. Samples for oil and grease, temperature, pH, cyanide, total phenols, sulfides, and volatile organic compounds must be obtained using grab collection techniques.

C. For sampling required in support of baseline monitoring and 90-day compliance reports required in Section 6.1 and 6.3 [40 CFR 403.12(b) and (d)], a minimum of four (4) grab samples must be used for pH, cyanide, total phenols, oil and grease, sulfide and volatile organic compounds for facilities for which historical sampling data do not exist; for facilities for which historical sampling data are available, Pretreatment Coordinator may authorize a lower minimum. For the reports required by paragraphs Section 6.4 (40 CFR 403.12(e) and 403.12(h)), the Industrial User is required to collect the number of grab samples necessary to assess and assure compliance by with applicable Pretreatment Standards and Requirements.

6.12 Date of Receipt of Reports

Written reports will be deemed to have been submitted on the date postmarked. For reports, which are not mailed, postage prepaid, into a mail facility serviced by the United States Postal Service, the date of receipt of the report shall govern.

6.13 Recordkeeping

Users subject to the reporting requirements of this ordinance shall retain, and make available for inspection and copying, all records of information obtained pursuant to any monitoring activities required by this ordinance, any additional records of information obtained pursuant to monitoring activities undertaken by the User independent of such requirements, and documentation associated with Best Management Practices established under Section 2.4C. Records shall include the date, exact place, method, and time of sampling, and the name of the person(s) taking the samples; the dates analyses were performed; who performed the analyses; the analytical techniques or methods used; and the results of such analyses. These records shall remain available for a period of at least three (3) years. This period shall be automatically extended for the duration of any litigation concerning the User or the Sanitary District of Hammond, or where the User has been specifically notified of a longer retention period by the Pretreatment Coordinator.

6.14 Certification Statements

Certification of Permit Applications, User Reports and Initial Monitoring Waiver—The following certification statement is required to be signed and submitted by Users submitting permit applications in accordance with Section 4.8; Users submitting baseline monitoring reports under Section 6.1B(5); Users submitting reports on compliance with the categorical Pretreatment Standard deadlines under Section 6; Users submitting periodic compliance reports required by Section 6.4 A–D, and Users

submitting an initial request to forego sampling of a pollutant on the basis of Section 6.4B(4).

- A. The following certification statement must be signed by an Authorized Representative as defined in Section 1.4C:

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

- B. Certification of Pollutants Not Present

Users that have an approved monitoring waiver based on Section 6.4B must certify on each report with the following statement that there has been no increase in the pollutant in its wastestream due to activities of the User.

Based on my inquiry of the person or persons directly responsible for managing compliance with the Pretreatment Standard for 40 CFR _____ [specify applicable National Pretreatment Standard part(s)], I certify that, to the best of my knowledge and belief, there has been no increase in the level of _____ [list pollutant(s)] in the wastewaters due to the activities at the facility since filing of the last periodic report under Section 6.4A and 40 CFR 403.12(e)(1).

SECTION 7—COMPLIANCE MONITORING

7.1 Right of Entry: Inspection and Sampling

The Pretreatment Coordinator, or designee, shall have the right to enter the premises of any User to determine whether the User is complying with all requirements of this ordinance and any individual wastewater discharge permit or general permit or order issued hereunder. Users shall allow the Pretreatment Coordinator, or designee, ready access to all parts of the premises for the purposes of inspection, sampling, records examination and copying, and the performance of any additional duties.

- A. Where a User has security measures in force which require proper identification and clearance before entry into its premises, the User shall make necessary arrangements with its security guards so that, upon presentation of suitable identification, the Pretreatment Coordinator, or designee, shall be

permitted to enter without delay for the purposes of performing specific responsibilities.

B. The Pretreatment Coordinator, or designee, shall have the right to set up on the User's property, or require installation of, such devices as are necessary to conduct sampling and/or metering of the User's operations.

C. The Pretreatment Coordinator may require the User to install monitoring equipment as necessary. The facility's sampling and monitoring equipment shall be maintained at all times in a safe and proper operating condition by the User at its own expense. All devices used to measure wastewater flow and quality shall be calibrated semiannually to ensure their accuracy.

D. Any temporary or permanent obstruction to safe and easy access to the facility to be inspected and/or sampled shall be promptly removed by the User at the written or verbal request of the Pretreatment Coordinator and shall not be replaced. The costs of clearing such access shall be born by the User.

E. Unreasonable delays in allowing the Pretreatment Coordinator, or designee, access to the User's premises shall be a violation of this ordinance.

F. The location of the monitoring facility shall provide ample room in or near the monitoring facility to allow accurate sampling and preparation of samples and analysis and whether constructed on public or private property, the monitoring facilities should be provided in accordance with the Pretreatment Coordinator's requirements and all applicable local construction standards and specifications, and such facilities shall be constructed and maintained in such manner so as to enable the Pretreatment Coordinator, or designee, to perform independent monitoring activities.

7.2 Search Warrants

If the Pretreatment Coordinator, or designee, has been refused access to a building, structure, or property, or any part thereof, and is able to demonstrate probable cause to believe that there may be a violation of this ordinance, or that there is a need to inspect and/or sample as part of a routine inspection and sampling program of the Sanitary District of Hammond designed to verify compliance with this ordinance or any permit or order issued hereunder, or to protect the overall public health, safety and welfare of the community, the Pretreatment Coordinator may seek issuance of a search warrant from the Hammond City Court of the City of Hammond Indiana.

SECTION 8—CONFIDENTIAL INFORMATION

Information and data on a User obtained from reports, surveys, wastewater discharge permit applications, individual wastewater discharge permits, general permits, and monitoring programs, and from the Pretreatment Coordinator's inspection and sampling

activities, shall be available to the public without restriction, unless the User specifically requests, and is able to demonstrate to the satisfaction of the Pretreatment Coordinator, that the release of such information would divulge information, processes, or methods of production entitled to protection as trade secrets under applicable State law. Any such request must be asserted at the time of submission of the information or data. When requested and demonstrated by the User furnishing a report that such information should be held confidential, the portions of a report which might disclose trade secrets or secret processes shall not be made available for inspection by the public, but shall be made available immediately upon request to governmental agencies for uses related to the NPDES program or pretreatment program, and in enforcement proceedings involving the person furnishing the report. Wastewater constituents and characteristics and other effluent data, as defined at 40 CFR 2.302 shall not be recognized as confidential information and shall be available to the public without restriction.

SECTION 9—PUBLICATION OF USERS IN SIGNIFICANT NONCOMPLIANCE

The Pretreatment Coordinator shall publish annually, in a newspaper of general circulation that provides meaningful public notice within the jurisdictions served by the Sanitary District of Hammond, a list of the Users which, at any time during the previous twelve (12) months, were in Significant Noncompliance with applicable Pretreatment Standards and Requirements. The term Significant Noncompliance shall be applicable to all Significant Industrial Users (or any other Industrial User that violates paragraphs (C), (D) or (H) of this Section) and shall mean:

- A. Chronic violations of wastewater discharge limits, defined here as those in which sixty-six percent (66%) or more of all the measurements taken for the same pollutant parameter taken during a six (6) month period exceed (by any magnitude) a numeric Pretreatment Standard or Requirement, including Instantaneous Limits as defined in Section 2;
- B. Technical Review Criteria (TRC) violations, defined here as those in which thirty-three percent (33%) or more of wastewater measurements taken for each pollutant parameter during a six (6) month period equals or exceeds the product of the numeric Pretreatment Standard or Requirement including Instantaneous Limits, as defined by Section 2 multiplied by the applicable criteria (1.4 for CBOD, TSS, fats, oils and grease, and 1.2 for all other pollutants except pH);
- C. Any other violation of a Pretreatment Standard or Requirement as defined by Section 2 (Daily Maximum, long-term average, Instantaneous Limit, or narrative standard) that the Pretreatment Coordinator determines has caused, alone or in combination with other discharges, Interference or Pass Through, including endangering the health of POTW personnel or the general public;
- D. Any discharge of a pollutant that has caused imminent endangerment to the public or to the environment, or has resulted in the Pretreatment Coordinator's exercise of its emergency authority to halt or prevent such a discharge;

E. Failure to meet, within ninety (90) days of the scheduled date, a compliance schedule milestone contained in an individual wastewater discharge permit or a general permit or enforcement order for starting construction, completing construction, or attaining final compliance;

F. Failure to provide within thirty (30) days after the due date, any required reports, including baseline monitoring reports, reports on compliance with categorical Pretreatment Standard deadlines, periodic self-monitoring reports, and reports on compliance with compliance schedules;

G. Failure to accurately report noncompliance; or

H. Any other violation(s), which may include a violation of Best Management Practices, which the Pretreatment Coordinator determines will adversely affect the operation or implementation of the local pretreatment program.

SECTION 10—ADMINISTRATIVE ENFORCEMENT REMEDIES

10.1 Notification of Violation

When the Pretreatment Coordinator finds that a User has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, the Pretreatment Coordinator may serve upon that User a written Notice of Violation. Within fifteen (15) days of the receipt of such notice, an explanation of the violation and a plan for the satisfactory correction and prevention thereof, to include specific required actions, shall be submitted by the User to the Pretreatment Coordinator. Submission of such a plan in no way relieves the User of liability for any violations occurring before or after receipt of the Notice of Violation. Nothing in this Section shall limit the authority of the Pretreatment Coordinator to take any action, including emergency actions or any other enforcement action, without first issuing a Notice of Violation.

10.2 Consent Orders

The Pretreatment Coordinator may enter into Consent Orders, assurances of compliance, or other similar documents establishing an agreement with any User responsible for noncompliance. Such documents shall include specific action to be taken by the User to correct the noncompliance within a time period specified by the document. Such documents shall have the same force and effect as the administrative orders issued pursuant to Sections 10.4 and 10.5 of this ordinance and shall be judicially enforceable.

10.3 Show Cause Hearing

The Pretreatment Coordinator may order a User which has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, to appear before the Board of Sanitary Commissioners of the Sanitary District of Hammond and show cause why the proposed enforcement action should not be taken. Notice shall be served on the User specifying the time and place for the meeting, the proposed enforcement action, the reasons for such action, and a request that the User show cause why the proposed enforcement action should not be taken. The notice of the meeting shall be served personally or by registered or certified mail (return receipt requested) at least thirty (30) days prior to the hearing. Such notice may be served on any Authorized Representative of the User as defined in Section 1.4C and required by Section 4.8A. A show cause hearing shall not be a bar against, or prerequisite for, taking any other action against the User.

10.4 Compliance Orders

When the Pretreatment Coordinator finds that a User has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, the Pretreatment Coordinator may issue an order to the User responsible for the discharge directing that the User come into compliance within a specified time. If the User does not come into compliance within the time provided, sewer service may be discontinued unless adequate treatment facilities, devices, or other related appurtenances are installed and properly operated. Compliance orders also may contain other requirements to address the noncompliance, including additional self-monitoring and management practices designed to minimize the amount of pollutants discharged to the sewer. A compliance order may not extend the deadline for compliance established for a Pretreatment Standard or Requirement, nor does a compliance order relieve the User of liability for any violation, including any continuing violation. Issuance of a compliance order shall not be a bar against, or a prerequisite for, taking any other action against the User.

10.5 Cease and Desist Orders

When the Pretreatment Coordinator finds that a User has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, or that the User's past violations are likely to recur, the Pretreatment Coordinator may issue an order to the User directing it to cease and desist all such violations and directing the User to:

- A. Immediately comply with all requirements; and

- B. Take such appropriate remedial or preventive action as may be needed to properly address a continuing or threatened violation, including halting operations and/or terminating the discharge. Issuance of a cease and desist order shall not be a bar against, or a prerequisite for, taking any other action against the User.

10.6 Administrative Fines

A. When the Pretreatment Coordinator finds that a User has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, the District Manager may fine such User in an amount not to exceed Two Thousand Five Hundred (\$2,500.00) Dollars. Such fines shall be assessed on a per-violation, per-day basis. In the case of monthly or other long-term average discharge limits, fines shall be assessed for each day during the period of violation.

B. Users desiring to dispute such fines must file a written request for the Pretreatment Coordinator to reconsider the fine along with full payment of the fine amount within thirty (30) days of being notified of the fine. Where a request has merit, the Pretreatment Coordinator may convene a hearing on the matter. In the event the User's appeal is successful, the payment, together shall be returned to the User. The Pretreatment Coordinator may add the costs of preparing administrative enforcement actions, such as notices and orders, to the fine.

C. Issuance of an administrative fine shall not be a bar against, or a prerequisite for, taking any other action against the User.

10.7 Emergency Suspensions

The Pretreatment Coordinator may immediately suspend a User's discharge, after informal notice to the User, whenever such suspension is necessary to stop an actual or threatened discharge, which reasonably appears to present, or cause an imminent or substantial endangerment to the health or welfare of persons. The Pretreatment Coordinator may also immediately suspend a User's discharge, after notice and opportunity to respond, that threatens to interfere with the operation of the POTW, or which presents, or may present, an endangerment to the environment.

A. Any User notified of a suspension of its discharge shall immediately stop or eliminate its contribution. In the event of a User's failure to immediately comply voluntarily with the suspension order, the Pretreatment Coordinator may take such steps as deemed necessary, including immediate severance of the sewer connection, to prevent or minimize damage to the POTW, its receiving stream, or endangerment to any individuals. The Pretreatment Coordinator may allow the

User to recommence its discharge when the User has demonstrated to the satisfaction of the Pretreatment Coordinator that the period of endangerment has passed, unless the termination proceedings in Section 10.8 of this ordinance are initiated against the User.

B. A User that is responsible, in whole or in part, for any discharge presenting imminent endangerment shall submit a detailed written statement, describing the causes of the harmful contribution and the measures taken to prevent any future occurrence, to the Pretreatment Coordinator prior to the date of any show cause or termination hearing under Sections 10.3 or 10.8 of this ordinance.

Nothing in this Section shall be interpreted as requiring a hearing prior to any Emergency Suspension under this Section.

10.8 Termination of Discharge

In addition to the provisions in Section 5.6 of this ordinance, any User who violates the following conditions is subject to discharge termination:

- A. Violation of individual wastewater discharge permit or general permit conditions;
- B. Failure to accurately report the wastewater constituents and characteristics of its discharge;
- C. Failure to report significant changes in operations or wastewater volume, constituents, and characteristics prior to discharge;
- D. Refusal of reasonable access to the User's premises for the purpose of inspection, monitoring, or sampling; or
- E. Violation of the Pretreatment Standards in Section 2 of this ordinance.

Such User will be notified of the proposed termination of its discharge and be offered an opportunity to show cause under Section 10.3 of this ordinance why the proposed action should not be taken. Exercise of this option by the Pretreatment Coordinator shall not be a bar to, or a prerequisite for, taking any other action against the User.

10.9 Falsifying of Information/ Tampering

Any person who knowingly makes any false statements, representation, record, report, plan or other document filed with the District or falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required under this Ordinance, or who falsely certifies any information shall be considered in violation of this Ordinance and is subject to enforcement up to and including criminal prosecution.

SECTION 11—JUDICIAL ENFORCEMENT REMEDIES

11.1 Injunctive Relief

When the Pretreatment Coordinator finds that a User has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement, the Pretreatment Coordinator may petition Hammond City Court through Sanitary District of Hammond's Attorney for the issuance of a temporary or permanent injunction, as appropriate, which restrains or compels the specific performance of the individual wastewater discharge permit, the general permit, order, or other requirement imposed by this ordinance on activities of the User. The Pretreatment Coordinator may also seek such other action as is appropriate for legal and/or equitable relief, including a requirement for the User to conduct environmental remediation. A petition for injunctive relief shall not be a bar against, or a prerequisite for, taking any other action against a User.

11.2 Civil Penalties

A. A User who has violated, or continues to violate, any provision of this ordinance, an individual wastewater discharge permit, or a general permit, or order issued hereunder, or any other Pretreatment Standard or Requirement shall be liable to the Sanitary District of Hammond for a minimum civil penalty of One Thousand (\$1,000.00) Dollars but not more than Twenty-Five Thousand (\$25,000.00) Dollars per violation, per day. In the case of a monthly or other long-term average discharge limit, penalties shall accrue for each day during the period of the violation.

B. The Sanitary District of Hammond may recover reasonable attorneys' fees, court costs, and other expenses associated with enforcement activities, including sampling and monitoring expenses, and the cost of any actual damages incurred by the Sanitary District of Hammond.

C. In determining the amount of civil liability, the Court shall take into account all relevant circumstances, including, but not limited to, the extent of harm caused by the violation, the magnitude and duration of the violation, any economic benefit gained through the User's violation, corrective actions by the User, the compliance history of the User, and any other factor as justice requires.

D. Filing a suit for civil penalties shall not be a bar against, or a prerequisite for, taking any other action against a User.

11.3 Criminal Prosecution

The District shall have the authority to seek criminal penalties in at least the amount of One Thousand (\$1,000.00) Dollars against a user who willfully or negligently violates

any provision of this ordinance, an individual wastewater discharge permit, or a general permit or order issued hereunder, or any other Pretreatment Standard or Requirement.

11.4 Remedies Nonexclusive

The remedies provided for in this ordinance are not exclusive. The Pretreatment Coordinator may take any, all, or any combination of these actions against a noncompliant User. Enforcement of pretreatment violations will generally be in accordance with the Sanitary District of Hammond's enforcement response plan. However, the Pretreatment Coordinator may take other action against any User when the circumstances warrant. Further, the Pretreatment Coordinator is empowered to take more than one enforcement action against any noncompliant User.

SECTION 12—AFFIRMATIVE DEFENSES TO DISCHARGE VIOLATIONS

12.1 Upset

A. For the purposes of this Section, upset means an exceptional incident in which there is unintentional and temporary noncompliance with categorical Pretreatment Standards because of factors beyond the reasonable control of the User. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.

B. An upset shall constitute an affirmative defense to an action brought for noncompliance with categorical Pretreatment Standards if the requirements of paragraph (C), below, are met.

C. A User who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:

- (1) An upset occurred and the User can identify the cause(s) of the upset;
- (2) The facility was at the time being operated in a prudent and workman-like manner and in compliance with applicable operation and maintenance procedures; and
- (3) The User has submitted the following information to the Pretreatment Coordinator within twenty-four (24) hours of becoming aware of the upset [if this information is provided orally, a written submission must be provided within five (5) days]:
 - (a) A description of the indirect discharge and cause of noncompliance;

- (b) The period of noncompliance, including exact dates and times or, if not corrected, the anticipated time the noncompliance is expected to continue; and
- (c) Steps being taken and/or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

D. In any enforcement proceeding, the User seeking to establish the occurrence of an upset shall have the burden of proof.

E. Users shall have the opportunity for a judicial determination on any claim of upset only in an enforcement action brought for noncompliance with categorical Pretreatment Standards.

F. Users shall control production of all discharges to the extent necessary to maintain compliance with categorical Pretreatment Standards upon reduction, loss, or failure of its treatment facility until the facility is restored or an alternative method of treatment is provided. This requirement applies in the situation where, among other things, the primary source of power of the treatment facility is reduced, lost, or fails.

12.2 Prohibited Discharge Standards

A User shall have an affirmative defense to an enforcement action brought against it for noncompliance with the general prohibitions in Section 2.1(A) of this ordinance or the specific prohibitions in Sections 2.1(B)(1) through (13) of this ordinance if it can prove that it did not know, or have reason to know, that its discharge, alone or in conjunction with discharges from other sources, would cause Pass Through or Interference and that either:

A. A Local Limit exists for each pollutant discharged and the User was in compliance with each limit directly prior to, and during, the Pass Through or Interference; or

B. No Local Limit exists, but the discharge did not change substantially in nature or constituents from the User's prior discharge when the Sanitary District of Hammond was regularly in compliance with its NPDES permit, and in the case of Interference, was in compliance with applicable sludge use or disposal requirements.

12.3 Bypass

A. For the purposes of this Section,

- (1) Bypass means the intentional diversion of wastestreams from any portion of a User's treatment facility.

- (2) Severe property damage means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

B. A User may allow any bypass to occur which does not cause Pretreatment Standards or Requirements to be violated, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provision of paragraphs (C) and (D) of this Section.

C. Bypass Notifications

- (1) If a User knows in advance of the need for a bypass, it shall submit prior notice to the Pretreatment Coordinator/District Manager at least ten (10) days before the date of the bypass, if possible.
- (2) A User shall submit oral notice to the Pretreatment Coordinator of an unanticipated bypass that exceeds applicable Pretreatment Standards within twenty-four (24) hours from the time it becomes aware of the bypass. A written submission shall also be provided within five (5) days of the time the User becomes aware of the bypass. The written submission shall contain a description of the bypass and its cause; the duration of the bypass, including exact dates and times, and, if the bypass has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the bypass. The Pretreatment Coordinator may waive the written report on a case-by-case basis if the oral report has been received within twenty-four (24) hours.

D. Bypass

- (1) Bypass is prohibited, and the Pretreatment Coordinator may take an enforcement action against a User for a bypass, unless
 - (a) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - (b) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and

- (c) The User submitted notices as required under paragraph (C) of this section.
- (2) The Pretreatment Coordinator may approve an anticipated bypass, after considering its adverse effects, if the Pretreatment Coordinator determines that it will meet the three conditions listed in paragraph (D)(1) of this Section.

SECTION 13—WASTEWATER TREATMENT RATES - [RESERVED]

SECTION 14—MISCELLANEOUS PROVISIONS

14.1 Pretreatment Charges and Fees

The Sanitary District of Hammond has established reasonable fees for reimbursement of costs of setting up and operating the Sanitary District of Hammond Pretreatment Program. They are:

- A. Wastewater discharge permit fees; due and payable to the District June 1st annually:

	<u>Permit Fee</u>
Annual Major User	\$1,500.00
Annual Minor User	\$ 300.00

Fees for wastewater discharge permit applications including the cost of processing such applications shall be One Hundred Dollars (\$100.00);

- B. Fees for each surveillance survey shall be Two Hundred Dollars (\$200.00) per sampling visit per day. Surveillance monitoring frequencies shall not be greater than those determined from the procedures set forth in the District's Enforcement Response Plan (ERP);
- C. Costs for the District's use of outside laboratory service shall be borne by the User, and shall be limited to the analytical fees required to verify and enforce compliance with Pretreatment Program.
- D. Fees for filing appeals;
- E. Fees to recover administrative and legal costs (not included in Section 14.1 B) associated with the enforcement activity taken by the Pretreatment Coordinator to address IU noncompliance.

14.2 Administrative Appeal

- A. All interpretations, decisions, findings and rulings of the Sanitary District of Hammond or its employees and representatives, shall be submitted to the User(s) in writing. All Notices of Violation shall refer to the Ordinance alleged to be violated and the specific sections or provisions thereof.
- B. At the User's request, the Sanitary District of Hammond shall meet and confer with any affected User to resolve any complaints, violations or problems arising out the administration and/or enforcement of this Ordinance.
- C. All decisions, findings, interpretations and requests by the Pretreatment Coordinator or his designee shall upon request of User, be reviewed and responded to in writing by the District Manager within thirty (30) days and shall be appealable by the User to the Board of Sanitary Commissioners of the Sanitary District of Hammond, who shall meet with the User and enter its findings and decisions in writing.
- D. All findings, orders, rulings and/or decisions of the Sanitary District of Hammond shall be appealable under the Administrative Adjudication Act of the State of Indiana. The transcript of the record and/or any evidence taken at the hearing shall be furnished by the Sanitary District of Hammond to be filed with the appropriate reviewing court. Requests for interpretations or decisions or the option of meetings between the District and a User does not stay enforcement proceedings or the User's duty to comply with pretreatment standards or requirements, Enforcement discretion is available to conform to a User's circumstances.

14.3 Severability

If any provision of this ordinance is invalidated by any court of competent jurisdiction, the remaining provisions shall not be affected and shall continue in full force and effect.

14.4 Recovery of Costs Incurred by the District and/or City

Any User violating any of the provisions of this Ordinance, or who fails to comply with the terms or conditions of their Wastewater Discharge Permit, or who discharges or causes a discharge producing a deposit or obstruction or caused damage to or impairs the POTW shall be liable to the District and/or City for any expense, loss or damage caused by such violation or discharge, including any expenses or fines associated with regulatory agency action related to such violation. The District and/or city shall bill the User for the costs proven to have been incurred by the District and/or City for any cleaning, repair or replacement work caused by the violation or discharges. All finding may be appealed to the POTW and to a court of competent jurisdiction. Refusal to pay the assessed costs shall constitute a violation of this Ordinance enforceable under the provisions of Section 10 of this Ordinance.

SECTION 15—EFFECTIVE DATE

This ordinance shall be in full force and effect immediately following its passage, approval, and publication, as provided by law.